



CH-01T712-48630-74K-A1XQ
RCV 400
Made in China

Li-ion
CE
RoHS

RECHARGABLE BATTERY
Model: PAB3A6019
Capacity: 48630mAh
Voltage: 11.1V
Nominal Voltage: 11.1V
Max. Charge Voltage: 12.6V
Min. Discharge Voltage: 9.0V
Operating Temperature: 0°C to 40°C
Storage Temperature: -20°C to 60°C
Do not expose to fire or high temperature.
Do not disassemble, modify, or damage the battery.
Do not use the battery if it is swollen, leaking, or damaged.
Do not use the battery if it is short-circuited or has a strong smell.
Do not use the battery if it is overcharged or over-discharged.
Do not use the battery if it is used in a non-approved device.
Do not use the battery if it is used in a non-approved environment.
Do not use the battery if it is used in a non-approved location.
Do not use the battery if it is used in a non-approved way.
Do not use the battery if it is used in a non-approved manner.
Do not use the battery if it is used in a non-approved way.
Do not use the battery if it is used in a non-approved manner.
Do not use the battery if it is used in a non-approved way.
Do not use the battery if it is used in a non-approved manner.

CAUTION
Do not use the battery if it is swollen, leaking, or damaged.
Do not use the battery if it is short-circuited or has a strong smell.
Do not use the battery if it is overcharged or over-discharged.
Do not use the battery if it is used in a non-approved device.
Do not use the battery if it is used in a non-approved environment.
Do not use the battery if it is used in a non-approved location.
Do not use the battery if it is used in a non-approved way.
Do not use the battery if it is used in a non-approved manner.
Do not use the battery if it is used in a non-approved way.
Do not use the battery if it is used in a non-approved manner.

Model: PAB3A6019
Capacity: 48630mAh
Voltage: 11.1V
Nominal Voltage: 11.1V
Max. Charge Voltage: 12.6V
Min. Discharge Voltage: 9.0V
Operating Temperature: 0°C to 40°C
Storage Temperature: -20°C to 60°C